

ARCHITECTURAL



65TRi25 Linear Drain

The 65TR25 is a standard style grate featuring a 3mm wire/5mm gap.

The 65TRi25 is a modular drainage kit with stainless steel grate(s), stainless steel drainage channel and fittings. All components are manufactured from 316 marine grade stainless steel. Please note that our TR grates have a non linished finish.

Stormtech Modular Kits are supplied with grate and oversized channel to be cut down on site. One piece channel comes with pre punched spigot with outlet extender (kits up to 2000mm long). Oversized channel enables choice of outlet positions: centre, end or wherever preferred. Kits over 2000mm long and kits requiring multiple outlets are supplied with outlet on joiner plate. All kits are supplied with 2x clip-on end caps.

Refer to AS3500 for outlet pipe sizes specific to your installation. (Grate/Channel Lengths Provided) 900mm/1500mm, 1000mm/1500mm, 1200mm/1800mm, 1500mm/2400mm, 1800mm/3000mm,...

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) 72mm 27mm 900mm 1000mm 1200mm 1500mm 1800mm 1900mm 2000mm DN50

Outlet Size

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage Threshold Drainage


Visit **stormtech.com.au** for tools + inspiration.

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 03/08/2025 (please check for updates)





Code 65TRi25 Range 65 Grate Style TR Category Modular Kits Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.