



125Custom-316-B

Linear Drain

316 stainless steel 125mm wide grate and custom channel depth.

Depth between 27mm and 135mm.

Available with a 5mm wire x 5mm gap or 5mm wire x 5mm gap GRATE GRIP slip resistant dimple finish

Suits Load Class B.

For site specific needs or unusual situations, choose from our Custom Fabrication range.


Stormtech can customise any drainage requirements to achieve maximum efficiency



Channel Material Stainless Steel **Steel Grade** 316

Code 125Custom-316-B

Range Custom Fabrication



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.


SPECIFICATIONS + DIMENSIONS

Channel Width 135mm

Channel Depth 27mm - 135mm **Length(s)** As Required

Outlet Size DN40, DN50, DN65, DN80, DN100

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

organization del grand del





Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 07/12/2025 (please check for updates)